

Lu Hai (lxh224@student.bham.ac.uk), Asaad Faramarzi, Nicole Metje  
University of Birmingham, School of Engineering, Edgbaston, Birmingham, UK

## 1. Contextual Background

- Increased urbanisation often requires **pile foundations** for high-rise buildings and critical infrastructure.
- This could impact existing buried assets including underground **tunnels** (Fig. 1).
- Previous study showed that with a minimum clearance of **12.9 m** between an existing tunnel and piles, the maximum horizontal movement of the tunnel reached **23.7 mm** [1].
- The **influence** on existing tunnels during a driven pile installation has not received sufficient attention.

## 2. Aim and Objectives

- Better understand the impact of driven pile installation on segmentally lined tunnels.
- Develop a methodology incorporating **physical testing** and **numerical modelling**.
- Analyse tunnel **response** of tunnel by parametric study.
- Assess the current **guidelines** for driven pile installation.






Fig. 1 Driving piles near existing segmentally lined tunnel (generated from OpenAI's ChatGPT).

## 3. Methodology

- Development of physical test processes using a small geotechnical **centrifuge** with a diameter of 1.5 m with extensive sensing (strain gauges, load cells, PIV) to monitor the tunnel-pile interaction.
- The **segmentally** lined tunnel is designed based on the equivalent bending stiffness [2].

## 3. Methodology (continue)

- Numerical modelling** considering more realistic conditions is validated where the pile installation is achieved using Arbitrary Lagrangian–Eulerian method [3].
- Parametric study** is conducted to evaluate the influence of the variables the variables involved in tunnel-pile interaction.




## 5. What's next

- Physical modelling using a geotechnical **centrifuge** to simulate in-situ earth pressure conditions.
- Comparative analysis of tunnel behaviour with **continuous lining and segmental** lining to evaluate joint influence.
- Advanced numerical modelling for investigation of **key factors** affecting tunnel response under pile-driving-induced loads.

## 4. Results

- Case study is conducted where pile and tunnel are **0.6 m**, **6.2 m** in diameter and **9 m** in clearance.
- Fig. 2 illustrates that the tunnel cross-section experiences **ovalisation** (timed by 100), which keeps **increasing** until penetration depth  $H$  is 19 m and then **decreases**.
- The peak of the maximum extension and contraction is **2.95 mm** and **-3.39 mm**, respectively.



- The tunnel exhibits consistent radial movement away from the pile, accompanied by settlement. Peak movements reach **9 mm** (horizontal) and **3.9 mm** (vertical) (Fig. 3 and Fig. 4 with  $H$  is the penetration depth).




Fig. 3 Tunnel horizontal movement




Fig. 4 Tunnel vertical movement

## References

- Liu, X., Sang, Y., Zhao, F., Shi, G., & Heng, Y. (2019). Evaluation of effects of static pile driving on existing metro tunnel structure. *J. of Performance of Constructed Facilities*, 33(4), 04019045.
- Fang, Q., Liu, X., Zeng, K., Zhang, X., Zhou, M., & Du, J. (2022). Centrifuge modelling of tunnelling below existing twin tunnels with different types of support. *Underground Space (China)*, 7(6), 1125–1138.
- Hai, L., Yensri, P., Faramarzi, A., & Metje, N. (2024). Numerical investigation of the interaction between existing tunnels and driven pile installation. In *Geotechnical Engineering Challenges to Meet Current and Emerging Needs of Society* (pp. 1644-1649). CRC Press.